□ DCS pro Specifications

Fucntions	FULL-HD Live Image (16:9) Comparison image USB2.0 PC Slave Mode Image Adgustment - Brightness, Sharpness, Contrast, Gamma, Exposure - Image Conversion - Selectable color mode(User 1/2/3/Default) - Storaged Image File Play - Create Folder, Delete Folder & File - System Time setting
Camera Resolution	1920x1080
Video Out	1920x1080i, 60 frame, HDMI
PC Interface	USB 2.0 / Slave Mode Directly connected to the PC application
Internl Storage	32G
Enternal Storage interface	USB 2.0 Memory Stic /FAT32
Still image Capture	1920x1080 jpg File
User Key Interface	5 Directional Key
Light Source	18W LED lamp, Color temperature (4800° K), Adjustable light intensity
Cable Length	2.0M
Foot switch	for Freeze & Still Capture
AC Input	90~264VAC Max 45Watt Universal AC Input / Full range
Dimension	Width(209mm) x Depth(101mm) x Height(250mm)

\square Moving Camera Stand Optional

- Hole the camera for still image
- Maintaining focus
- Angle control lever
- Easy moving







SOMETECH INC.

(Ace High-end Tower ||, Guro-dong) 1201ho, 1204ho, 61, Digital-ro 26gil, Guro-gu, Seoul, Korea

TEL: +82-2-2025-1000(Rep.) FAX: +82-2-2025-1009 E-mail: overseas@sometech.com / www.sometech.com

MEDICAL CAMERA SYSTEM



- **:: Full HD**(1080i 60 Frames)
- **::** Telemedicine system















- Video Rectoscope
- Endoscopic camera system
- Video Dermascope
- Video Otoscope
- Video Irisscope
- Video scope for optician











Main features

• Optimal solution for Telemedicine system



This is the most suitable medical camera for telemedicine system that enables remote-imaging treatment and prescription through network provided by qualified medical professionals.


Convenient joystick

Convenient joystic with each directions can lead to freeze, save and zoom images conveniently.



Image management


- · Captured images can be selectively saved onto internal memory (SD CARD) or USB.
- It can be connected to PC via USB port and manage saved images on main units more efficiently.
- · Various comparison and display. (1 to 4 frame)



X Zoom IN/OUT (X1.0 - X3.0)

• Full HD(1080i / 60 Frames)

Image quality comparison



[640 x 480] [1280 x 720] Full HD[1920 x 1080]

Image Conversion

Image can be conversed in various ways



• 18W LED Lamp loaded


18W LED Lamp is brighter than 100W Halogen Lamp. 4800° K color temperature close to natural light makes it possible to realize clearer image than Halogen lamp.

Easy Connection with PC/Laptops

DCS pro can be easily connected to a computer via USB 2.0. Users can save digital data on a computer.



Applications with various accessories



· Check on contact lens, conjunctivitis

and Iris.

(* Magnification specified by 24" TV Monitor)

Contact lens test CAP

x30

x60